

HemoCue® Hb 201 DM System



Lab-quality hemoglobin results at the point of care

Hb 201 DM


The HemoCue® Hb 201 DM System brings your practice lab-quality hemoglobin results to the point of care. The system has added controls and advanced data management capabilities, including QC lockout and built-in barcode scanning*. These features support data integrity and privacy, along with bi-directional communication and flexible settings.

Improve your administrative workflow

- Seamlessly interface with existing network using POCT1-A
- Simplify billing
- Ensure regulatory compliance

Safeguard patient testing and data

- Link patient information and comments with test result
- Reduce errors with automatic result transfer
- Gain full data storage



HemoCue OnCue™ Support

HemoCue OnCue™ Support is a comprehensive program designed to meet your needs as quickly and conveniently as possible.

Powered by HemoCue employees, you get answers and education from the experts who know our products best.

Get easy access to lab-quality accuracy

- Precise factory calibration against the ICSH reference method
- Microcuvette technology with excellent lot-to-lot reproducibility
- Brief training with virtually no maintenance

HemoCue® Hb 201 DM System

Specifications¹

Principle

Modified azidemethemoglobin reaction; dual wavelengths (570 nm and 880 nm) for compensation of turbidity

Calibration

Factory calibrated against the ICSH reference method; needs no further calibration

Sample material

Capillary, venous or arterial whole blood

Measurement range

0-25.6 g/dL (0-256 g/L, 0-15.9 mmol/L)

Results

15-60 seconds

Sample volume

10 µL

Dimensions

Analyzer: 6.70 x 3.66 x 1.97 inches
(170 x 93 x 50 mm)

Docking station: 8.10 x 5.30 x 2.40 inches
(206 x 135 x 61 mm)

Weight

Analyzer: 0.77 lbs (350 g) with batteries installed
Docking station: 1.24 pounds (566 g)

Storage temperature

Analyzer: 32-122°F (0-50°C)

Microcuvettes: unopened 59-86 °F (15-30 °C);
three-month open vial stability

Operating temperature

64-86°F (18-30°C)

Power

Internal rechargeable Li-ion batteries or docking station with AC adapter

Quality control

Built-in self-test, system can be verified using liquid controls

Interface

USB/LAN POCT1-A

Data entry

Touch-screen display

Built-in barcode scanner*

*LASER LIGHT

DO NOT STARE INTO BEAM
CLASS 2 LASER PRODUCT




CPT codes


85018-QW: Blood count; hemoglobin (hgb)

The CPT codes provided are based on AMA guidelines and are for informational purposes only. CPT coding is the sole responsibility of the billing party. Please direct any questions regarding coding to the payer being billed.


Get results in simple steps




1 Fill the microcuvette.



2 Place the microcuvette into the analyzer.



3 View results.



4 Seamlessly interface with your network.

¹ HemoCue® Hb 201 DM System package insert 151743 211004