

# HemoCue<sup>®</sup> WBC System



### From assessment to treatment - faster

WBC

Based on HemoCue's proven, reliable microcuvette technology, the HemoCue® WBC System brings you the unique benefit of determining total white blood cell counts right at the point of care. In just three minutes, you have results with the same precision and accuracy as those from a central laboratory.

Fitting seamlessly into a variety of clinical applications and even remote field clinics, the benefits are clear. Immediate WBC counts can mean the difference between waiting and taking action at the point of care – helping you move from assessment to treatment within minutes rather than hours or days.

#### Answers right when you need them

- Lab-accurate results in minutes
- Faster treatment decisions and streamlined workflow
- Easy to use by healthcare professionals and laboratory personnel
- Capillary or venous samples

#### Accuracy for confident decisions

- Factory calibration with no further calibration needed
- Unique software for internal QC
- Blood-based liquid controls available



### HemoCue<sup>®</sup> WBC System

Specifications

Principle Imaging system characterizing white cells that are stained and counted

Calibration Factory calibrated; needs no further calibration

Sample material Capillary or venous (EDTA) whole blood

Measurement range 0.3-30.0×10<sup>9</sup>/L (300-30000/mm³, 300-30000/μL)

Measuring time Within 3 minutes

Sample volume 10  $\mu L$ 

**Dimensions** 179×133×121 mm (7.05×5.24×4.76 inches)

Weight 600 g (1.32 pounds) with batteries installed


Storage temperature Analyzer: 0-50 °C (32-122 °F) Microcuvettes: 15-35 °C (59-95 °F), <90% non-condensing humidity; short-term storage (four weeks, unopened) 0-50 °C (32-122 °F), <90% non-condensing humidity; three-month open vial stability

**Operating temperature** 15-35 °C (59-95 °F) Power

Power adapter or batteries (6 AA alkaline batteries)


Interface Printer and PC

Quality control Built-in self-test; three levels of liquid controls available



Comparison study between HemoCue WBC and Sysmex XS-1000i, venous samples.


## Three simple steps



**1** Fill microcuvette.



2 Place microcuvette into analyzer.



3 View results.

HemoCue AB Kuvettgatan 1 SE-262 71 Ängelholm Sweden

Phone: +46 431 48 12 00 E-mail: info@hemocue.se Org. No: 556342-9272 GPM324INT 240712